



OSNOVNA PLOŠČA 1700 ASUS ROG STRIX Z790-A GAMING WIFI II ATX 1XHDMI 2.1 1XDISPLAYPORT 1.4

Vaša cena: 339,00€

Šifra: 340660

Kategorija: [MB 1700](#)

EAN: 4711387340660

OPIS

PODNOŽJE: INTEL LGA1700

ZA PROCESORJE: Intel 12/13/14th Generation Core™ i7/i5/i3/Pentium/Celeron

FORMAT: ATX Form Factor 30.5 x 24.4 cm

VEZNI ČIP: Intel Z790 Express

POMNILNIK:

4 x DDR5

(8000+(OC)/7800(OC)/7600(OC)/7400(OC)/7200(OC)/7000(OC)/6800(OC)/6600(OC)/6400(OC)/6200(OC)/ 6000(OC)/ 5800(OC)/ 5600/ 5400/ 5200/ 5000/ 4800MHz) do skupno 192GB kapacitete, dual channel in Extreme Memory Profile (XMP) OptiMem II podpora, ASUS Enhanced Memory Profile II (AEMP II)

GRAFIKA: preko CPU

RAID: DA (0,1,5,10)

RAZŠIRITVENE REŽE:

1 x PCIe 5.0/4.0/3.0 x16 (x16 mode)

1 x PCIe 4.0 x16 slot (supports x4 mode)

1 x PCIe 3.0 x1 slots

MREŽNA KARTICA: Intel 2.5GbE LAN chip ASUS LANGuard + 2x2 Intel Wi-Fi 7 supporting 2.4/5/6 GHz + BLUETOOTH 5.4

ZVOČNA KARTICA: ROG SupremeFX 5.1 Surround Sound High Definition Audio CODEC ALC4080



NOTRANJI PRIKLJUČKI:

Fan and Cooling Related

- 1 x 4-pin CPU Fan header
- 1 x 4-pin CPU OPT Fan header
- 1 x 4-pin AIO Pump header
- 5 x 4-pin Chassis Fan headers

Power Related

- 1 x 24-pin main power connector
- 2 x 8-pin +12V power connector

Storage Related

- 5 x M.2 slots (Key M)
- 4 x SATA 6Gb/s ports

USB

- 1 x USB 20Gbps connector (supports USB Type-C®)
- 1 x USB 5Gbps header supports 2 additional USB 5Gbps ports
- 2 x USB 2.0 headers support 4 additional USB 2.0 ports

Miscellaneous

- 3 x Addressable Gen 2 headers
- 1 x Aura RGB header
- 1 x CPU Over voltage jumper
- 1 x Front panel audio header (F_AUDIO)
- 1 x 20-3 pin system panel header with Chassis intrude function
- 1 x Thermal sensor header
- 1 x Thunderbolt™ (USB4®) header

ZUNANJI PRIKLJUČKI:

- 1 x USB 20Gbps port (1 x USB Type-C®)
- 3 x USB 10Gbps ports (2 x Type-A+1 x USB Type-C®)
- 4 x USB 5Gbps ports (4 x Type-A)
- 4 x USB 2.0 ports (4 x Type-A)
- 1 x DisplayPort
- 1 x HDMI™ port
- 1 x Wi-Fi module
- 1 x Intel® 2.5Gb Ethernet
- 2 x Audio jacks
- 1 x Optical S/PDIF out port
- 1 x BIOS FlashBack™ button
- 1 x Clear CMOS button

DODATNO:

- Extreme Engine Digi+
- 5K Black metallic capacitors
- ASUS Q-Design



- M.2 Q-Latch
- PCIe Slot Q-Release
- Q-Antenna
- Q-DIMM
- Q-LED (CPU [red], DRAM [yellow], VGA [white], Boot Device [yellow green]) with DRAM Detection
- Q-Slot

ASUS Thermal Solution

- M.2 heatsink backplate
- M.2 heatsink
- VRM heatsink design

ASUS EZ DIY

- BIOS FlashBack™ button
- BIOS FlashBack™ LED
- Clear CMOS button
- CPU Socket lever protector
- ProCool II
- Pre-mounted I/O shield
- SafeSlot
- SafeDIMM

Aura Sync

- Aura RGB header
- Addressable Gen 2 headers

Front Panel USB 20Gbps with PD Fast Charge Support

- Support: up to 30W charging
- Support: USB power delivery notification with power output wattage display
- Output: 5V/9V max. 3A, 12V max 2.5A
- Compatible with PD3.0

Software Features

ROG Exclusive Software

- ROG CPU-Z
- DTS® Sound Unbound

ASUS Exclusive Software

Armoury Crate

- AIDA64 Extreme (60 days free trial)
- Aura Creator
- Aura Sync
- Fan Xpert 4 (with AI Cooling II)
- GameFirst
- Power Saving
- Sonic Studio
- Two-Way AI Noise Cancelation



AI Suite 3

- Easy Optimization with AI Overclocking
- TPU
- DIGI+ VRM
- Turbo app
- PC Cleaner

MyASUS

USB Wattage Watcher

Intel® Unison™

Adobe Creative Cloud (Free Trial)

Norton 360 for Gamers (60 Days Free Trial)

WinRAR (40 Days Free Trial)

UEFI BIOS

AI Overclocking Guide

ASUS EZ DIY

- ASUS CrashFree BIOS 3
- ASUS EZ Flash 3
- ASUS UEFI BIOS EZ Mode
- ASUS MyHotkey

FlexKey

MemTest86

Spletna stran

proizvajalca: <https://rog.asus.com/motherboards/rog-strix/rog-strix-z790-a-gaming-wifi-ii/>

KATALOGI IN NAVODILA ZA UPORABO

1. <https://cdn.e-misija.si/pdf/340660-navodila.pdf>

TEHNIČNI PODATKI

PODATKI PROIZVAJALCA

Asus Global PTE. LTD.

No. 15, Li-De Road, Beitou District, Taipei 112

Taiwan

email@asus.com

<https://www.asus.com/>



Zastopnik za EU:

ASUS Europe B.V.
Paasheuvelweg 25, Amsterdam 1105
The Netherlands
service@asus.de

Obvestila in varnostna opozorila:

