



OSNOVNA PLOŠČA 1700 GIGABYTE Z790 AORUS ELITE AX ATX 1XHDMI 1XDISPLAYPORT

Vaša cena: 244,65€

[IZENAČIM CENO](#)

Šifra: 849467

Kategorija: [MB 1700](#)

EAN: 4719331849467

OPIS

PODNOŽJE: INTEL LGA1700

ZA PROCESORJE: Intel 12/13th Generation Core™ i7/i5/i3/Pentium/Celeron

FORMAT: ATX Form Factor 30.5 x 24.4 cm

VEZNI ČIP: Intel Z790 Express

POMNILNIK:

4 x DDR5 (7600(O.C.) /7400(O.C.) /7200(O.C.) /7000(O.C.) /6800(O.C.) /6600(O.C.) / 6400(O.C.) / 6200(O.C.) / 6000(O.C.) / 5800(O.C.) / 5600(O.C.) / 5400(O.C.) / 5200(O.C.) / 4800 / 4000MHz) do skupno 128GB kapacitete, dual channel in Extreme Memory Profile (XMP) podpora, Support for non-ECC / ECC Un-buffered DIMM (operate in non-ECC mode), Support for ECC Un-buffered DIMM 1Rx8/2Rx8 memory modules (operate in non-ECC mode), Support for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules

GRAFIKA: preko CPU

RAID: DA (0,1,5,10)

RAZŠIRITVENE REŽE:

1 x PCIe 5.0/4.0/3.0 x16 (x16 mode)

2 x PCIe 3.0 x16 (x4 mode)

MREŽNA KARTICA: Realtek® 2.5GbE LAN chip (2.5 Gbps/1 Gbps/100 Mbps) + Wi-Fi 6E AX211 WIFI a, b, g, n, ac, ax, supporting 2.4/5/6 GHz + BLUETOOTH 5.3

ZVOČNA KARTICA: Realtek® High Definition Audio Audio CODEC



NOTRANJI PRIKLJUČKI:

- 1 x 24-pin ATX main power connector
- 2 x 8-pin ATX 12V power connectors
- 1 x CPU fan header
- 1 x water cooling CPU fan header
- 3 x system fan headers
- 1 x system fan/water cooling pump header
- 2 x addressable LED strip headers
- 2 x RGB LED strip headers
- 4 x M.2 Socket 3 connectors
- 6 x SATA 6Gb/s connectors
- 1 x front panel header
- 1 x front panel audio header
- 1 x USB Type-C® header, with USB 3.2 Gen 2 support
- 1 x USB 3.2 Gen 1 header
- 2 x USB 2.0/1.1 headers
- 2 x Thunderbolt™ add-in card connectors
- 1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0 module only)
- 1 x reset button
- 1 x Q-Flash Plus button
- 1 x Clear CMOS button
- 1 x reset jumper
- 1 x Clear CMOS jumper

ZUNANJI PRIKLJUČKI:

- 1 x USB Type-C® port, with USB 3.2 Gen 2x2 support
- 2 x USB 3.2 Gen 2 Type-A ports (red)
- 3 x USB 3.2 Gen 1 ports
- 4 x USB 2.0/1.1 ports
- 2 x SMA antenna connectors (2T2R)
- 1 x HDMI 2.0 port
- 1 x DisplayPort
- 1 x RJ-45 port
- 1 x optical S/PDIF Out connector
- 2 x audio jacks

DODATNO:

- iTE® I/O Controller Chip
- H/W Monitoring
- Voltage detection
- Temperature detection
- Fan speed detection
- Water cooling flow rate detection



Fan fail warning
Fan speed control
BIOS
1 x 256 Mbit flash
Use of licensed AMI UEFI BIOS
PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0
Unique Features
Support for GIGABYTE Control Center (GCC)
Support for Q-Flash
Support for Q-Flash Plus
Support for Smart Backup
Bundled Software
Norton® Internet Security (OEM version)
LAN bandwidth management software

Spletna stran proizvajalca: <https://www.gigabyte.com/Motherboard/Z790-AORUS-ELITE-AX-rev-10#kf>

KATALOGI IN NAVODILA ZA UPORABO

- <https://cdn.e-misija.si/pdf/849467-navodila.pdf>

TEHNIČNI PODATKI

PODATKI PROIZVAJALCA

Giga-Byte Technology Co., Ltd.
No.6, Bao Chiang Road, 231 NEW TAIPEI CITY
Taiwan
<https://www.gigabyte.com/>

Zastopnik za EU:

Ernst Reiner GmbH & Co. KG
Baumannstr. 16, Furtwangen
Germany
info@siewert-kau.de



Obvestila in varnostna opozorila:

