



**OSNOVNA PLOŠČA
LGA1851GIGABYTE B860 DS3H
WIFI6E ATX HDMI DP**

Vaša cena: 170,33€

[IZENAČIM CENO](#)

Šifra: B860-DS3H-Wifi

Kategorija: [MB 1851](#)

EAN: 4719331867515

OPIS

PODNOŽJE: INTEL LGA 1851

ZA PROCESORJE: Intel® Core™ Ultra Processors

FORMAT: ATX format 30.5 cm x 24.4 cm

VEZNI ČIP: INTEL B860

POMNILNIK:

4 x DDR5 DIMM ECC/non-ECC 9066(O.C)/8800(O.C) /8600(O.C) / 8400(O.C) /8266(O.C) / 8200(O.C) / 8000(O.C) / 7950(O.C) / 7900(O.C) / 7800(O.C) / 7600(O.C.) / 7400(O.C.) / 7200(O.C.) / 7000(O.C.) / 6800(O.C.) / 6600(O.C.) / 6400 / 5600MHz) do skupno 256GB kapacitete, dual channel in XMP podpora, ECC/non-ECC podpora

GRAFIKA: DA - preko CPU

RAID: RAID 0, RAID 1, RAID 5, and RAID 10

RAZŠIRITVENE REŽE:

1 x PCI Express 5.0 x16

4 x PCI Express 4.0 x1

MREŽNA KARTICA: Realtek 2.5GbE LAN chip + Intel Wi-Fi 6E AX211 WIFI a, b, g, n, ac, ax + BLUETOOTH 5.3

ZVOČNA KARTICA: Realtek codec High Definition Audio (2/4/5.1/7.1-channel)

NOTRANJI PRIKLJUČKI:

1 x 24-pin ATX main power connector



- 1 x 8-pin ATX 12V power connector
- 1 x CPU fan header
- 1 x CPU fan/water cooling pump header
- 2 x system fan headers
- 2 x system fan/water cooling pump headers
- 3 x addressable RGB Gen2 LED strip headers
- 1 x RGB LED strip header
- 2 x M.2 Socket 3 connectors
- 4 x SATA 6Gb/s connectors
- 1 x front panel header
- 1 x front panel audio header
- 1 x S/PDIF Out header
- 1 x USB Type-C® header, with USB 3.2 Gen 1 support
- 1 x USB 3.2 Gen 1 header
- 2 x USB 2.0/1.1 headers
- 1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0/GC-TPM2.0 SPI V2 module only)
- 1 x serial port header
- 1 x Q-Flash Plus button
- 1 x reset jumper
- 1 x Clear CMOS jumper

ZUNANJI PRIKLJUČKI:

- 1 x PS/2 keyboard/mouse port
- 1 x HDMI port
- 1 x DisplayPort
- 1 x USB Type-C® port, with USB 3.2 Gen 2x2 support
- 1 x USB 3.2 Gen 2 Type-A port (red)
- 4 x USB 2.0/1.1 ports
- 1 x RJ-45 port
- 2 x antenna connectors (2T2R)
- 3 x audio jacks

DODATNO:

- iTE® I/O Controller Chip
- H/W Monitoring
- Voltage detection
- Temperature detection
- Fan speed detection
- Water cooling flow rate detection
- Fan fail warning
- Fan speed control
- BIOS



1 x 256 Mbit flash
Use of licensed AMI UEFI BIOS
PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0
Unique Features
Support for GIGABYTE Control Center (GCC)
Support for Q-Flash
Support for Q-Flash Plus
Support for Smart Backup
Bundled Software
Norton® Internet Security (OEM version)
LAN bandwidth management software

Spletna stran proizvajalca: <https://www.gigabyte.com/Motherboard/B860-DS3H-WIFI6E/sp#sp>

TEHNIČNI PODATKI

PODATKI PROIZVAJALCA

Giga-Byte Technology Co., Ltd.
No.6, Bao Chiang Road, 231 NEW TAIPEI CITY
Taiwan
<https://www.gigabyte.com/>

Zastopnik za EU:

Ernst Reiner GmbH & Co. KG
Baumannstr. 16, Furtwangen
Germany
info@siewert-kau.de



Obvestila in varnostna opozorila:

