



UPS BATERIJA HITACHI-CSB /12V 9,0AH (HRL 1234W)

Vaša cena: 45,11€

[IZENAČIM CENO](#)

Šifra: HRL1234W

Kategorija: [UPS](#)

EAN: 3830078311237

OPIS

Standarna dodatna baterija za UPS naprave, priporočamo jo za Socomec UPS-e. HRL 1234W F2FR je baterija s podaljšano življenjsko dobo. Prenese več kot 260 ciklov popolnega praznjenja in polnjenja in v stanju pripravljenosti ima življenjsko dobo predvidoma 8 let.

Njene lastnosti so majhen volumen, nizka teža in več ciklov polnjenja in praznjenja, kot običajne baterije.

Tehnični opis proizvajalca v angleškem jeziku:

Cells Per Unit	6
Voltage Per Unit	12 V
Capacity	34W @ 15 Minute-Rate to 1.67V Per Cell @ 25°C(77°F)
Weight	Approx. 2.7 kg(5.95 lbs)
Maximum Discharge Current	130A (5 Sec)
Internal Resistance Approx.	Approx. 17 mΩ



Operating Temperature Range	Discharge $-15^{\circ}\text{C} \sim 50^{\circ}\text{C}$ ($5^{\circ}\text{F} \sim 122^{\circ}\text{F}$) Charge $-15^{\circ}\text{C} \sim 40^{\circ}\text{C}$ ($5^{\circ}\text{F} \sim 104^{\circ}\text{F}$) Storage $-15^{\circ}\text{C} \sim 40^{\circ}\text{C}$ ($5^{\circ}\text{F} \sim 104^{\circ}\text{F}$)
Nominal Operating Temperature Range	$25^{\circ}\text{C} \pm 3^{\circ}\text{C}$ ($77^{\circ}\text{F} \pm 5^{\circ}\text{F}$)
Float Charging Voltage	13.5 to 13.8 VDC/Unit Average at 25°C (77°F)
Recommended Maximum Charging Current Limit	3.4A
Equalization and Cycle Service	14.4 to 15.0 VDC/Unit Average at 25°C (77°F)

PODATKI PROIZVAJALCA

Hitachi, Ltd.
6-6, Marunouchi 1-chome, Chiyoda-ku, Tokyo 100-8280
Japan
inquiry@hitachi.com
<https://www.hitachi.com/>

Zastopnik za EU:

Hitachi Europe Ltd.
Whitebrook Park, Lower Cookham Road, Maidenhead, Berkshire SL6 8YA
United Kingdom
info.uk@hitachi-eu.com

Obvestila in varnostna opozorila:

